

Flex-Rite™



...for visual accuracy of product levels and flow.

VuFlo® flow indicator allows quick verification of product volume and transfer through your system. Chemically resistant and designed to produce excellent performance in Dairy, Food & Beverage, Cosmetics, Pharmaceutical and Biotech applications. (Meets 3-A*, USDA, FDA and USP Class VI standards).

Features/Benefits:

- Transparent / Clean Viewing
- Full Pressure Flow
- Chemical Resistant
- Rated for High/Low Temps
- Resists Cross-Contamination
- Non-Discoloring
- Insensitive to Ultraviolet or sunlight
- Universal Applications
- Shatterproof
- Excellent Endurance

MODEL	I.D.	O.D.	WORKING PRESSURE	WEIGHT PER FT.	VACUUM IN HG.
VFI050	1/2"	.72"	200 PSI	.18 LB	27
VFI075	3/4"	1.02"	175 PSI	.33 LBS	27
VFI100	1"	1.27"	125 PSI	.43 LBS	27
VFI150	1 1/2"	1.82"	105 PSI	.74 LBS	27
VFI200	2"	2.27"	75 PSI	.80 LBS	27

TUBE: Class VI, FEP RECOMMENDED CLEANING: CIP, COP, SIP TEMP. RANGE: -80 to 450° F

2 1/2" - 3" - 4" Available Upon Request - Consult Factory

V-Series Products meet/comply: USDA Class III requirements, FDA CFR Title 21 177.2600, 3-A 20-23

*The 3-A 62-02, standard applies only to assemblies of 3/4" diameter and larger.

WARNING: Work pressure ratings for all Flex-Rite™ Products are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "V" series applications that exceed 275°F contact manufacturer for suggestions.

