

Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: True Tap® HD

Product Number (s): 03400, 03401, 03403, 03404

Manufactured By:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

General Information
Technical Assistance
(800) 521-3168
Customer Service
(800) 272-4620
24-Hr Emergency (CHEMTREC)
(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Amber liquid, wintergreen odor

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE: May cause mild to moderate irritation.

SKIN: May cause mild irritation with extended contact.

INHALATION: Inhalation of oil mist is harmful and may cause damage if TLV is exceeded.

INGESTION: May cause nausea.

CHRONIC EFFECTS: Unknown

TARGET ORGANS: Unknown

Medical Conditions Aggravated by Exposure:

pre-existing skin disorders

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Chlorinated paraffin	63449-39-8	45 - 55	
Glycerol ester of fatty acids	proprietary	30 - 40	
Hydrotreated light naphthenic distillate	64742-53-6	0 - 5	
Methyl salicylate	119-36-8	< 1	

Section 4: First Aid Measures

Product Name: True Tap® HD

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician

if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do not induce vomiting unless directed by medical personnel. Never give anything by mouth

to an unconscious person.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

<u>Flammable Properties</u>: As defined by OSHA, this product is nonflammable.

Flash Point: 415 F (PMCC) Upper Explosive Limit: ND Autoignition Temperature: ND Lower Explosive Limit: ND

Suitable Extinguishing Media: Foam or dry chemical

Products of Combustion: Oxides of carbon

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye

and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product

decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined

space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using

an absorbent designed for chemical spills. Place used absorbents into

proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Use as directed. Normal safety precautions common to good manufacturing should be

followed.

Storage Procedures: Store in a cool dry area out of direct sunlight. Keep containers closed when not in use.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Chlorinated paraffin	NE	NE	NE	NE	5	mfr	mg/m ³
Glycerol ester of fatty acid	NE	NE	NE	NE	NE		
Hydrotreated light naphthenic distillate	5*	NE	5*	NE	NE		mg/m ³
Methyl salicylate	NE	NE	NE	NE	NE		
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated * - oil mist							

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow

applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering

controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained

breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or Viton. Also, use full protective clothing if there is

prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid

Color: amber Odor: wintergreen

Product Name: True Tap® HD Product Number (s): 03400, 03401, 03403, 03404

Specific Gravity: 1.108 Initial Boiling Point: 212 F

Freezing Point: ND

Vapor Pressure: < 1 mmHg @ 68 F Vapor Density: < 1 (air = 1) Evaporation Rate: < 1 (ether = 1)

Solubility: negligible in water

pH: NA

Volatile Organic Compounds: wt %: <1 g/L: <60 lbs./gal: < 0.5

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: None known.

Incompatible Materials: Strong acids and bases.

Hazardous Decomposition Products: Oxides of carbon.

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

Component	<u>Test</u>	Result	<u>Route</u>	<u>Species</u>
Chlorinated paraffin Chlorinated paraffin	LD50	> 10 mL/kg	Dermal	Rabbit
	LD50	26100 mg/kg	Oral	Rat

CHRONIC EFFECTS

Carcinogenicity:

Component Result

OSHA: Chlorinated paraffin Hazard Communication Carcinogen IARC: Chlorinated paraffin 2B – Possibly carcinogenic to humans

NTP: None listed

Mutagenicity: No information available

Other: None

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available

Product Name: True Tap® HD Product Number (s): 03400, 03401, 03403, 03404

Persistence / Degradability: No information available Bioaccumulation / Accumulation: No information available No information available

Section 13: Disposal Considerations

Disposal: The material, as packaged, is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)

If this material is mixed with other materials, such as certain heavy metals, the resulting waste should be

evaluated for waste classification.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Not Regulated

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

<u>Toxic Substances Control Act (TSCA)</u>:

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard No

Reactive Hazard No
Release of Pressure No
Acute Health Hazard Yes
Chronic Health Hazard Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting

requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:

polychlorinated alkanes (< 55%)

Clean Air Act:

Product Name: True Tap® HD

Section 112 Hazardous Air Pollutants (HAPs): None

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: 119-36-8 Pennsylvania: 119-36-8 Massachusetts: 119-36-8 Rhode Island: 119-36-8

Additional Regulatory Information: None

Section 16: Other Information

NFPA: Health: 1 Flammability: 1 Reactivity: 1

HMIS: Health: 1 Flammability: 1 Reactivity: 1 PPE: B

Prepared By: Michelle Rudnick

CRC #: 03400 Revision Date: 04/29/2009

Changes since last revision: Changed ™ in product name to ®.

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable Parts per Million ND: Not Determined ppm: TCC: Tag Closed Cup NE: Not Established Pensky-Martens Closed Cup PMCC: g/L: grams per Liter PPE: Personal Protection Equipment lbs./gal: pounds per gallon

TWA: Time Weighted Average STEL: Short Term Exposure Limit

OSHA: Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists

NIOSH National Institute of Occupational Safety & Health